Distributed by Blulinc

TECHNICAL DATA SHEET · 22 KW

Autel AC Single Charger LCD

Flexible 22 kW AC charger with LCD display and Eichrecht metering.



KEY POINTS

- Max. 22kW
- 1 charge point(s)
- LCD display, 4G
- PTB/Eichrecht compliant metering
- IP54, IK10
- 36-month standard warranty, extendable to 5 years

SPECIFICATIONS

Charge points	**1**
Connector	**Type-2 socket**
Dimensions (HxWxD)	**315 x 170 x 107mm**
Display	**LCD**
Grid connection	**Single phase, three phase or Delta grid up to 32A**
Output power	**Max. 22kW**
Electronic protection	**AC 30mA, DC 6mA**
Protection rating	**IP54, IK10**
Supported protocols	**OCPP 1.6J / 2.0.1; Modbus RTU / TCP**
Connectivity	**4G, Wi-Fi, Ethernet, Bluetooth, Wi-SUN, RS-485**
Energy metering	**PTB/Eichrecht compliant meter**
Mounting	**Wall or pedestal**
Weight	**2,5kg (charger), 2kg (SJB)**
Warranty	**36 months, extendable to 5 years**

Who it is for

Public charge points in Germany and locations where a simple LCD display is enough.

Connection

An ordinary single phase or three phase connection up to 32 amps, as in a home or small office.

ABOUT THIS CHARGER

This version of the Autel AC Single Charger up to 22 kW has a clear LCD display for direct readout of kWh consumption and charge status, instead of the 5-inch touchscreen. The PTB/Eichrecht compliant metering makes it suitable for public charge points in Germany. Otherwise identical to the standard Single Charger: Smart Junction Box for fast installation, dynamic load balancing, 4G and OCPP 1.6J / 2.0.1. Supplied as standard with a Type-2 socket; a fixed cable is only available on request from 30 units.

Official Autel distributor Benelux
Blulinc NV, Booiebos 8A, 9031 Drongen
BE0775669111

Advice and quote
autel@blulinc.com
autelcharging.com

Specifications according to official Autel data. Subject to change.