Distributed by Blulinc

TECHNICAL DATA SHEET · 22 KW

Autel AC Single Charger

Flexible 22 kW AC charger with Smart Junction Box.



KEY POINTS

- Max. 22kW
- 1 charge point(s)
- OCPP 1.6J / 2.0.1
- IP54, IK10
- 36-month standard warranty, extendable to 5 years

SPECIFICATIONS

Charge points	**1**
Connector	**Type-2 socket**
Dimensions (HxWxD)	**315 x 170 x 107mm**
Display	**5-inch touchscreen or LCD**
Grid connection	**Single phase, three phase or Delta grid up to 32A**
Output power	**Max. 22kW**
Electronic protection	**AC 30mA, DC 6mA**
Protection rating	**IP54, IK10**
Supported protocols	**OCPP 1.6J / 2.0.1; Modbus RTU / TCP**
Connectivity	**4G, Wi-Fi, Ethernet, Bluetooth, Wi-SUN, RS-485**
Energy metering	**MID-meter**
Mounting	**Wall or pedestal**
Weight	**2,5kg (charger), 2kg (SJB)**
Warranty	**36 months, extendable to 5 years**

Who it is for

Offices, apartment buildings and company car parks with several cars.

Connection

An ordinary single phase or three phase connection up to 32 amps, as in a home or small office.

ABOUT THIS CHARGER

The Autel AC Single Charger is a powerful, flexible charging solution up to 22 kW, available with a 5-inch touchscreen or LCD. The Smart Junction Box allows pre-installation: the charger clicks onto the SJB and can be commissioned in bulk, which makes installation fast and cost efficient. Dynamic load balancing, real-time notifications, remote updates and ISO 15118-2/20 compatibility make it future proof. Supplied as standard with a Type-2 socket; a fixed cable is only available on request from 30 units.

Official Autel distributor Benelux
Blulinc NV, Booiebos 8A, 9031 Drongen
BE0775669111

Advice and quote
autel@blulinc.com
autelcharging.com

Specifications according to official Autel data. Subject to change.