Distributed by Blulinc

TECHNICAL DATA SHEET · 2X22 KW

# Autel AC Ultra

Dual AC charger, 2 x 22 kW, with 8 inch touchscreen.




KEY POINTS

- 2x 22kW
- 2 charge point(s)
- OCPP 1.6J / 2.0.1
- IP54, IK10
- 36-month standard warranty, extendable to 5 years

SPECIFICATIONS

| | |
|---|---|
| Charge points | **2** |
| Connectors | **2x Type-2 sockets** |
| Dimensions (HxWxD) | **625 x 320 x 170mm** |
| Display | **8 inch (1280x720)** |
| Grid connection | **63A** |
| Output power | **2x 22kW** |
| Protection | **2x RCBO C40A/30mA type A + 2x DC 6mA** |
| Protection rating | **IP54, IK10** |
| Supported protocols | **OCPP 1.6J / 2.0.1; Modbus RTU / TCP** |
| Connectivity | **4G, Wi-Fi, Ethernet, RS-485** |
| Energy metering | **MID-meter** |
| Payment terminal | **Optional** |
| Mounting | **Wall or pedestal** |
| Weight | **15kg (charger), 25kg (pedestal)** |
| Warranty | **36 months, extendable to 5 years** |

### Who it is for

Offices, apartment buildings and company car parks with several cars.

### Connection

A three phase connection. Your electrician sets the cable size and the fuse.

ABOUT THIS CHARGER

The Autel AC Ultra is a powerful AC charger with up to 22 kW per charge point. It complies with ISO 15118-2/20, which enables Plug & Charge and V2G. This versatile charger mounts on a pedestal or on a wall. The 8 inch touchscreen shows all session information and can play advertising for extra revenue. Available as a wall model or with a black back-to-back pedestal, with or without payment terminal. Supplied as standard with 2 Type-2 sockets; a fixed cable is only available on request from 30 units.

**Official Autel distributor Benelux**

Blulinc NV, Booiebos 8A, 9031 Drongen
BE0775669111

**Advice and quote**

autel@blulinc.com
autelcharging.com

Specifications according to official Autel data. Subject to change.