Distributed by Blulinc

TECHNICAL DATA SHEET · 400 KW/LAADPUNT

Autel DT500

Air cooled dispenser up to 400 kW per charge point.



KEY POINTS

- 400kW per charge point
- 1 or 2 charge point(s)
- OCPP 1.6J or 2.0.1
- IP55, IK10
- 24-month standard warranty, extendable to 10 years

SPECIFICATIONS

Charge points	**1 or 2**
Connector	**2x CCS2**
Dimensions (HxWxD)	**1650x322x322mm**
Display	**8 inch (1920x1080)**
Max. output power	**400kW per charge point**
Charging current	**380A (max 500A)**
Protection rating	**IP55, IK10**
Backoffice protocol	**OCPP 1.6J or 2.0.1**
Connectivity	**Ethernet**
Energy metering	**MID-meter**
Cooling	**Luchtgekoeld**
Payment terminal	**Optional**
Cable	**5m (7,5m optional)**
Weight	**160kg**
Warranty	**24 months, extendable to 10 years**

Who it is for

Charging hubs, transport and public fast charging with many cars a day.

Connection

A heavy feed or a dedicated transformer. This needs to be agreed with the grid operator.

ABOUT THIS CHARGER

The Autel DT500 offers flexible output up to 400 kW per charge point. It comes with 2 air cooled CCS2 connectors and an 8 inch touchscreen, with an optional payment terminal. Available with 1 or 2 charge points. Works together with a DS power cabinet (DS480, DS960 or DS1440).

Official Autel distributor Benelux
Blulinc NV, Booiebos 8A, 9031 Drongen
BE0775669111

Advice and quote
autel@blulinc.com
autelcharging.com

Specifications according to official Autel data. Subject to change.