Distributed by Blulinc

TECHNICAL DATA SHEET · 480 KW/LAADPUNT

Autel DT800

Liquid cooled dispenser up to 480 kW per charge point.



KEY POINTS

- 480kW per charge point
- 1 or 2 charge point(s)
- OCPP 1.6J or 2.0.1 (optional)
- IP55, IK10
- 24-month standard warranty, extendable to 10 years

SPECIFICATIONS

Charge points	**1 or 2**
Connector	**2x CCS2**
Dimensions (HxWxD)	**1950x322x322mm**
Display	**8 inch (1920x1080)**
Max. output power	**480kW per charge point**
Charging current	**500A (max 650A)**
Protection rating	**IP55, IK10**
Backoffice protocol	**OCPP 1.6J or 2.0.1 (optional)**
Connectivity	**Ethernet**
Energy metering	**MID-meter**
Cooling	**Vloeistofgekoeld**
Payment terminal	**Optional**
Cable	**5m (7,5m optional)**
Weight	**200kg**
Warranty	**24 months, extendable to 10 years**

Who it is for

Charging hubs, transport and public fast charging with many cars a day.

Connection

A heavy feed or a dedicated transformer. This needs to be agreed with the grid operator.

ABOUT THIS CHARGER

The Autel DT800 liquid cooled dispenser offers flexible output up to 480 kW per charge point. It has 2 liquid cooled CCS2 connectors, an 8 inch touchscreen and an optional payment terminal. Available with 1 or 2 charge points. Works together with a DS power cabinet (DS480, DS960 or DS1440).

Official Autel distributor Benelux
Blulinc NV, Booiebos 8A, 9031 Drongen
BE0775669111

Advice and quote
autel@blulinc.com
autelcharging.com

Specifications according to official Autel data. Subject to change.